

TECHNICAL DATA SHEET VV 430 RP

Rev 01

ARTICLE CODE

VV 430 RP

PATTERN

Reps

FINISH

Loomstate / Silan

COMPOSITION

100% Glass fiber

TECHNICAL DATA	VALUE	STANDARD
Nominal weight (g/sqm)	430 ± 5%	ISO 3374
Standard width (mm) ¹	1240 ± 1,5%	UNI EN 1773
Fabrick thickness (mm) ²	0,36 *	UNI EN ISO 5084

Measured between selvedges

^{*}indicative date

CONSTRUCTION		
	Warp	Weft
Material	EC 9 3x204	EC 9 68
Setting (thr/cm)	5 ± 5% [ISO 4602 (TA)]	6,8 ± 5% [ISO 4602 (TA)]
Weight ditribution (%)	50	50

FIBER PROPERTIES			
	Warp	Weft	
Nominal Yield ²	204 Tex	204 Tex	
Fiber density ²³	n.g.	n.g.	
Twist ²	n.g.	n.g.	

²Depending on order and yarn specification

ADDITIONAL INFORMATION

NOTE: All technical information contained in this document are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any contract. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. The information contained herein is under constant review and liable to be modified. All products are sold subject to Microtex Composites Srl terms and conditions of sale. Copyright 2020 - Microtex Composites Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.

Doc no. TDS-F_1 Rev 01 Issued 28/01/2021 Author L. Gucci





³No measure, certified by supplier