

ARTICLE CODE	VV 600 8HS
PATTERN	Satin 8H—Raso da 8
FINISH	Loomstate / Silan
COMPOSITION	100% Glass fiber

TECHNICAL DATA	VALUE	STANDARD
Nominal weight (g/sqm)	600 ± 5%	ISO 3374
Standard width (mm) ¹	1250 ± 1,5%	UNI EN 1773
Fabrick thickness (mm) ²	-	UNI EN ISO 5084

Measured between selvages

*indicative date

CONSTRUCTION		
	Warp	Weft
Material	Roving 300 Tex E- Glass	Roving 300 tex E-Glass
Setting (thr/cm)	10 ± 5% [ISO 4602 (TA)]	9.8 ± 5% [ISO 4602 (TA)]
Weight ditribution (%)	51	49

FIBER PROPERTIES		
	Warp	Weft
Nominal Yield ²	600 Tex	600 Tex
Fiber density ²³	n.g.	n.g.
Twist ²	n.g.	n.g.

²Depending on order and yarn specification

³No measure, certified by supplier

ADDITIONAL INFORMATION

Coupling agent: Silane

Type of sizing is suitable for UP - EP - VE resins

NOTE: All technical information contained in this document are given in good faith and are based on tests believed to be reliable, but their accuracy and completeness are not guaranteed. They do not constitute an offer to any person and shall not be deemed to form the basis of any contract. Accordingly, the user shall determine the suitability of the products for their intended use prior to purchase and shall assume all risk and liability in connection therewith. The information contained herein is under constant review and liable to be modified. All products are sold subject to Microtex Composites Srl terms and conditions of sale. Copyright 2020 - Microtex Composites Srl. All rights reserved worldwide. All trademarks or registered trademarks are the property of their respective owners.

Doc no. TDS-F_1
Rev 00
Issued 30/11/2018
Author L. Gucci